



> PRINT > COPY > SCAN > FAX

ECOSYS M2030dn PN
ECOSYS M2030dn
ECOSYS M2530dn

A4 BLACK AND WHITE
MULTIFUNCTIONALS

PROFESSIONAL MULTIFUNCTIONALS YOU CAN RELY ON



- > Up to 30 A4 pages per minute
- > Time to first copy: 6.9 seconds
- > 5-line LCD display for clear messages and ease of use
- > Print, copy, scan and fax* functionality as standard
- > Duplex unit for cost-saving double-sided printing
- > 50-sheet document processor scans double-sided originals**

*Only ECOSYS M2530dn. **Not available for ECOSYS M2030dn PN.

These compact A4 MFPs can increase the productivity of any office. They have print and copy speeds of up to 30 pages per minute, and a time to first print of only 6.9 seconds. A large-capacity document processor makes light work of scanning double-sided originals, increasing throughput and maximising workflow. Integral time saving functions are easily accessed through a user friendly display and control panel.



ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required and the integrated system software provides long-term cross-network compatibility. KYOCERA's long life components cost you and the environment less.

GENERAL

Technology: KYOCERA ECOSYS Laser
Control panel display: 5-line LCD display
Engine speed: Up to 30 pages A4 per minute
Resolution: 1,200 dpi quality (1,800 x 600 dpi, print), 600 x 600 dpi, 256 greyscales (scan/copy)
Duty cycle:
 Maximum. 20,000 pages per month
 Maximum average. 2,000 pages per month
 Average. 1,666 pages per month
Warm-up time: Approx. 20 seconds or less
Time to first print: Approx. 7 seconds or less
Time to first copy: Approx. 6.9 seconds
CPU: PowerPC 465 S/667 MHz
Memory: Standard 512 MB, max. 1,536 MB
Standard interface: USB 2.0 (Hi-Speed), USB Host (High Speed), 10 Base-T/100 Base-TX/1000 Base-T, slot for optional SD-card, slot for optional print server (not in ECOSYS M2530dn)
Integrated accounting: 100 department codes
Dimensions (W x D x H):
 ECOSYS M2030dn PN: 494 x 410 x 366 mm
 ECOSYS M2030dn, M2530dn: 494 x 430 x 448 mm
Weight: ECOSYS M2030dn PN: Approx. 15 kg
 ECOSYS M2030dn / M2530dn: Approx. 18 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
ECOSYS M2030dn PN/M2030dn/M2530dn:
 Copying/Printing: 431 W
 Ready mode: 62 W
 Sleep mode: 3.7 W
 Plug-in off mode: 0.3 W or less
Noise (sound pressure level ISO 7779/ISO 9296):
ECOSYS M2030dn PN/M2030dn/M2530dn:
 Copying/Printing: Half-speed mode 49 dB(A) LpA
 Copying/Printing: Full-speed mode 50,9/50,4/50,4 dB(A) LpA
 Standby (Ready mode): 28,3/28,3/27,5 dB(A) LpA
Safety standards: TÜV/GS, CE
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: 50-sheet multi-purpose tray, 60 – 220 g/m², A4, A5, A6, B5, Letter, Legal, Folio, OF2, envelopes, Custom (70 x 148 to 216 x 356 mm) 250-sheet universal

paper cassette, 60 – 120 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm)
Max. input capacity with options: 800 sheets
Duplex unit: Duplex as standard supports 60 – 105 g/m²
Platen glass: Up to 216 x 356 mm
Reversing document processor (not available in ECOSYS M2030dn PN): 50-sheet, simplex scan 50 – 120 g/m², duplex scan 50 – 110 g/m², A4, A5, B5, Letter, Legal, Custom (140 x 210 to 216 x 356 mm)
Output capacity: Max. 150 sheets face-down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIe
Emulations: PCL6 (5c/XL), KPDL 3 (PostScript 3-compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF Direct Print Vers. 1.7, XPS Direct Print (requires memory expansion)
Operating systems: All current Windows operating systems, MAC OS X version 10.4 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 93 outline fonts (PCL 6, HP-compatible) + 8 (Windows Vista), 101 (KPDL3), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)
Features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3 and Private Print (requires memory expansion), IPPS, HTTPS, POP over SSL, AirPrint, SMT over SSL, FTP over SSL, LDAP over SSL

COPY FUNCTIONS

Max. original size: A4/Legal
Continuous copying: 1 – 999
Zoom range: 25 – 400% in 1% steps
Preset magnification ratios: 7 Reductions/5 Enlargements
Exposure mode: Auto, manual: 5 steps
Image adjustments: Text + photo, text, photo
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail, Scan-to-FTP (FTP over SSL), Scanto-SMB, Scan to USB Host, TWAIN (USB), WSD (WIA) scan (USB)
Scan speed: 35 ipm (300 dpi, A4, b/w), 14 ipm (300 dpi, A4, colour)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)
Max. scan size: A4, Legal
Original recognition: Text, photo, text + photo, for OCR

COMMAND CENTER RX

Command Centre RX enables control and management of various settings by accessing the device via a common web browser. It automatically updates screens, customises user screens, and displays department and restriction settings.

USB INTERFACE FOR USB FLASH MEMORY DEVICE

Documents can be printed directly from a USB flash memory device via the USB host interface. You can select documents stored as PDF, XPS, TIFF or JPEG directly on the printer's control panel. No computer is required.

File types: TIFF, PDF, JPEG, XPS, PDF/A
Compression method: MMR/JPEG
Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi-send (e-mail, fax, SMB/FTP folder, print) at once

FAX FUNCTIONS (ECOSYS M2530dn ONLY)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Less than 3 seconds
Scanning speed: 2.5 seconds
One-touch dial: 22 numbers
Address book: 200 entries
Maximum original size: A4, Legal
Compression method: JBIG, MMR, MR, MH
Memory reception: 256 sheets or more
Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast, memory reception

OPTIONS


Paper handling:
PF-120 Paper feeder: Max. 250 sheets, 60–120 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)
Memory: MDD3-1GB (DDR3)
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available
Optional interfaces:
(ECOSYS M2030dn PN and - M2030dn only)
IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)
IB-51: Wireless LAN (802.11b/g/n)
CB-120: Wooden desk with storage capacity, including castors (wheels)

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752
TK-1130 Toner-Kit: Microfine toner for 3,000 pages A4
 Capacity of starter toner is 1,000 pages A4

WARRANTY

2-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.



KYOCERA Document Solutions Europe (UK) Ltd,
 Eldon Court, 75-77 London Road, Reading RG1 5BS
 Tel: 0118 931 1500 – Fax: 0118 931 1108
www.kyoceradocumentsolutions.co.uk – info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

*Features/performance which requires a document processor is not offered by the ECOSYS M2030dn PN.
 **Depending on the country.

YOUR KYOCERA BUSINESS PARTNER

